

International Application Number: PCT/US98/23433

International Filing Date: 3 November 1998 (03.11.98)

Priority Date: 08/988,300 10 December 1997 (10.12.97) US

Applicant: CISCO TECHNOLOGY, INC. [US/US]; 170 West Tasman Drive, San Jose, CA 95134 (US).

Inventors: HUGHES, David, A.; 900 High School Way #2200, Mountain View, CA 94041 (US). CHOI, Isaac, P.; 205 Ellbridge Court, San Jose, CA 95123 (US). PADMANABHAN, Radhika; 4199 Monet Circle, San Jose, CA 95136 (US). FERNANDES, Neufin, L.; 7506 Shadowhill Lane, Cupertino, CA 95014 (US). BUCKLEY, William, P.; 6556 Jernnie Court, San Jose, CA 95120 (US). LAWRENCE, Jeremy, R.; 319 N. Third Street #2, San Jose, CA 95112 (US).

Agents: VINCENT, Lester, J. et al.; Blakely, Sokoloff, Taylor & Zafman, 7th floor, 12400 Wilshire Boulevard, Los Angeles, CA 90025-1026 (US).

(81) Designated States: AU, CA, JP, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).


Published

With international search report.

Title: A CONNECTION CONTROL INTERFACE FOR MULTISERVICE SWITCHES

Abstract

A connection control interface for a network is provided. The connection control interface allows the multiservice switch to provide a number of switch resource partitions to a number of independent controllers coupled to the switch. Switch resource partitions comprise a number of subsets of switch resources that are a number of independent subsets of a physical network. The connection control interface allows the independent controllers to control the connections on a switch using the number of switch resource partitions. The independent controllers each use one of a number of control systems comprising network software level. The independent controllers comprise a virtual switch architecture having a master component and a slave component where the master and slave components may be hosted on different processors. The slave components may be hosted on a control card that contains a number of port cards of the switch and a port card processor. The switch reconfigures the independent controllers are reconfigured when discrepancies are detected between the connections on the switch and expected by the each of the plurality independent controllers.



RE

BEST AVAILABLE COPY